


**D314(R-4)**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
<b>D314(R-4)</b>	16.9-24	10	146A8	TL	1310	429	26.0	32/220	3000/6610	40/25	15.00
		12	149A8	TL	1310	429	26.0	38/260	3250/7160	40/25	15.00
		14	152A8	TL	1310	429	26.0	46/320	3550/7825	40/25	15.00
	17.5L-24	6	132A8	TL	1241	445	26.0	20/140	2000/4400	40/25	15.00
		12	148A8	TL	1241	445	26.0	38/260	3150/6940	40/25	15.00
	19.5L-24	12	151A8	TL	1314	495	27.4	34/230	3450/7600	40/25	17.00
	21L-24	12	155A8	TL	1378	533	27.8	32/220	3875/8540	40/25	18.00
	18.4-26	12	156A8	TL	1425	467	27.0	36/250	4000/8820	40/25	16.00
	16.9-28	12	152A8	TL	1410	429	26.9	38/260	3550/7825	40/25	15.00
		16	156A8	TL	1410	429	26.9	44/300	4000/8815	40/25	15.00
18		160A8	TL	1410	429	26.9	49/340	4500/9920	40/25	15.00	