

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rządowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
230/95R36 130D 145A2 Performer 95	238	1352	639	4157	W8	W7

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)								
	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		2060	2220	2395	2595	2755	2900	3065	3230
10	1850	2025	2220	2395	2595	2755	2900		
25	1440	1575	1725	1860	2015	2140	2255		
30	1395	1525	1670	1805	1955	2075	2185		
40	1330	1455	1595	1720	1865	1975	2085		
50	1275	1395	1530	1650	1785	1895	1995		
65	1215	1325	1455	1570	1700	1805	1900		

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.