

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rządowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
230/95R48 136D 150A2 Performer 95	238	1657	784	5102	W8	W7

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)								
	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		2465	2635	2815	3000	3200	3410	3610	3810
10	2160	2365	2540	2765	3000	3180	3350		
25	1715	1875	2015	2195	2375	2520	2655		
30	1665	1820	1955	2130	2305	2445	2580		
40	1585	1730	1860	2025	2195	2330	2455		
50	1520	1660	1785	1945	2105	2235	2355		
65	1445	1580	1700	1850	2005	2125	2240		

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.