

# PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rzędowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

## Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
<b>270/95R38 140D 154A2</b> <b>Performer 95</b>	285	1478	700	4540	W9	W8, W10

## Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)								
	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		2715	2905	3105	3315	3560	3770	4015	4250
10	2390	2615	2815	3060	3315	3560	3750		
25	1890	2065	2225	2420	2620	2815	2965		
30	1835	2005	2155	2345	2545	2730	2875		
40	1745	1910	2055	2235	2420	2600	2740		
50	1675	1830	1970	2145	2320	2490	2625		
65	1595	1745	1875	2040	2210	2375	2500		

(\*): Cyclic Application (see note)

Note:

- \* Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- \* Vehicles must be unloaded before transport outside the field.
- \* Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- \* Maximum load per tyre includes all possible field and vehicle/usage variations.
- \* For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- \* Basic inflation pressure must be increased as per tables.