

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rzędowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
270/95R44 142D 156A2 Performer 95	275	1632	772	5025	W9	W8, W10

Tabela Obciążenia i Ciśnienie

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)									
		1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		2885	3085	3300	3570	3880	4055	4300	4505	
10	2555	2795	3005	3295	3570	3880	4000			
25	2005	2195	2360	2585	2805	3045	3140			
30	1945	2130	2290	2510	2720	2955	3050			
40	1855	2030	2180	2390	2590	2815	2905			
50	1780	1945	2090	2295	2485	2700	2785			
65	1695	1850	1990	2185	2365	2570	2650			

(*): Cyclic Application (see note)

Note:
* Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
* Vehicles must be unloaded before transport outside the field.
* Maximum load may not be carried for more than 1.5 km before unloading operation begins.
* Maximum load per tyre includes all possible field and vehicle/usage variations.
* For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
* Basic inflation pressure must be increased as per tables.