

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rzędowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
300/95R46 148D 162A2 Performer 95	306	1738	822	5343	W10	W9, DW10, DW11, W11

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)								
	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		3420	3715	4010	4290	4550	4795	5075	5355
10	3065	3390	3680	3975	4250	4510	4750		
25	2410	2665	2890	3125	3340	3545	3735		
30	2340	2585	2810	3035	3240	3440	3625		
40	2230	2465	2675	2890	3085	3275	3450		
50	2135	2365	2565	2770	2960	3140	3310		
65	2035	2250	2440	2635	2820	2990	3150		

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.