

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rzędowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
340/85R48 151D 165A2 Performer 85	353	1797	850	5525	W12	W11

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)							
	1.2	1.6	2.0	2.4	2.8	3.6	4.0	4.5
10*		3435	3825	4205	4535	5190	5495	5865
10	2905	3405	3765	4120	4485	5150		
25	2310	2705	2990	3275	3565	4090		
30	2240	2625	2900	3175	3460	3970		
40	2135	2500	2760	3025	3290	3780		
50	2045	2395	2650	2900	3160	3625		
65	1945	2280	2520	2765	3005	3450		

(*): Cyclic Application (see note)

Note:
* Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
* Vehicles must be unloaded before transport outside the field.
* Maximum load may not be carried for more than 1.5 km before unloading operation begins.
* Maximum load per tyre includes all possible field and vehicle/usage variations.
* For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
* Basic inflation pressure must be increased as per tables.