

MAXI TRACTION



- Stworzone do ciągników o dużej mocy, kombajnów i żniwiarek
- Podwyższone indeksy nośności i prędkości
- Doskonała trakcja, samooczyszczanie się i komfort prowadzenia
- Długa żywotność opony i równomierne zużywanie się bieżnika

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
600/65R30 155D 152E Maxi Traction	608	1538	695	4630	DW20B	DW18L - W18L

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)												
	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0
10+	3150	3655	4000	4300	4575	4875	5200	5515	5750	5970	6185	6390	6590
10	3150	3530	3860	4155	4520	4865	5125	5365	5595	5815			
30	2415	2710	2960	3185	3465	3730	3930	4115	4290	4460			
40	2300	2580	2820	3035	3300	3550	3740	3920	4085	4245			
50	2205	2475	2705	2910	3165	3405	3585	3755	3920	4070			
65		2355	2575	2770	3015	3245	3415	3580	3730	3875			
70		2180	2385	2565	2790	3000	3130	3280	3420	3550			

(*) : Cyclic Application (see note)

Note: * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
 * Vehicles must be unloaded before transport outside the field.
 * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
 * Maximum load per tyre includes all possible field and vehicle/usage variations.
 * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
 * Basic inflation pressure must be increased as per tables.