

MAXI TRACTION



- Stworzone do ciągników o dużej mocy, kombajnów i żniwiarek
- Podwyższone indeksy nośności i prędkości
- Doskonała trakcja, samooczyszczanie się i komfort prowadzenia
- Długa żywotność opony i równomierne zużywanie się bieżnika

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
600/70R28 157D 154E Maxi Traction	610	1557	704	4668	DW20B	DW18L - W18L

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)												
	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0
10+	2875	3415	3905	4355	4855	5330	5610	6040	6255	6460	6650	6835	7015
10	2875	3415	3905	4355	4855	5330	5565	5785	5995	6190			
30	2205	2620	2995	3340	3720	4085	4265	4435	4595	4745			
40	2100	2495	2850	3180	3545	3890	4065	4225	4375	4520			
50	2015	2390	2735	3050	3395	3730	3895	4050	4195	4335			
65		2280	2605	2905	3235	3555	3710	3860	3995	4125			
70		2070	2365	2640	2940	3230	3375	3505	3635	3750			

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.