

# MAXI TRACTION



- Stworzone do ciągników o dużej mocy, kombajnów i żniwiarek
- Podwyższone indeksy nośności i prędkości
- Doskonała trakcja, samooczyszczanie się i komfort prowadzenia
- Długa żywotność opony i równomierne zużywanie się bieżnika

## Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
620/70R42 166D 163E Maxi Traction	638	1930	873	5814	DW20B	DW18L - W18L

## Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)												
	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0
10+	3430	4075	4800	5480	6135	6760	7095	7665	7960	8240	8510	8765	9010
10	3430	4075	4800	5480	6135	6760	7090	7395	7680	7950			
30	2630	3125	3680	4205	4705	5185	5435	5670	5890	6095			
40	2505	2980	3505	4000	4480	4935	5175	5395	5605	5805			
50	2405	2855	3360	3840	4295	4735	4960	5175	5375	5565			
65		2720	3200	3655	4090	4510	4725	4930	5120	5300			
70		2500	2945	3360	3760	4145	4345	4535	4710	4875			

(\*): Cyclic Application (see note)

Note:

- \* Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- \* Vehicles must be unloaded before transport outside the field.
- \* Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- \* Maximum load per tyre includes all possible field and vehicle/usage variations.
- \* For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- \* Basic inflation pressure must be increased as per tables.