

MAXI TRACTION



- Stworzone do ciągników o dużej mocy, kombajnów i żniwiarek
- Podwyższone indeksy nośności i prędkości
- Doskonała trakcja, samooczyszczanie się i komfort prowadzenia
- Długa żywotność opony i równomierne zużywanie się bieżnika

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
620/75R30 163D 160E Maxi Traction	620	1687	764	5083	DW20B	-

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)												
	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0
10+	3535	4095	4585	5035	5445	5830	6275	6665	7030	7390	7705	7970	8290
10	3535	4095	4585	5035	5445	5830	6225	6605	6965	7315			
30	2710	3140	3515	3860	4175	4470	4775	5065	5340	5610			
40	2580	2990	3350	3675	3975	4255	4545	4820	5085	5340			
50	2475	2865	3210	3525	3815	4080	4360	4625	4880	5120			
65		2730	3060	3355	3630	3885	4150	4405	4645	4875			
70		2520	2825	3100	3350	3590	3830	4065	4290	4500			

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.