

MAXI TRACTION



- Stworzone do ciągników o dużej mocy, kombajnów i żniwiarek
- Podwyższone indeksy nośności i prędkości
- Doskonała trakcja, samooczyszczanie się i komfort prowadzenia
- Długa żywotność opony i równomierne zużywanie się bieżnika

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
620/75R30 168A8 168B Maxi Traction	653	1705	764	5083	DW20B	-

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)												
	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.4	3.6	4.0
10+	4095	4575	5040	5495	5955	6335	6700	7370	7955	8535	8780	9020	9520
10	3630	4105	4540	4940	5315	5670	5980	6550	7075	7560			
30	2880	3255	3600	3915	4215	4495	4740	5190	5605	5995			
40	2690	3040	3365	3660	3940	4200	4430	4850	5240	5600			
50	2690	3040	3365	3660	3940	4200	4430	4850	5240	5600			

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.

Maximum Speed	% change in loads from 40 km/h load	Changes in Infl. Pressure
10	+ 70%	+0.4 bar