

MAXI TRACTION



- Stworzone do ciągników o dużej mocy, kombajnów i żniwiarek
- Podwyższone indeksy nośności i prędkości
- Doskonała trakcja, samooczyszczanie się i komfort prowadzenia
- Długa żywotność opony i równomierne zużywanie się bieżnika

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
650/75R32 172A8 172B Maxi Traction	671	1801	810	5389	DW21B	DW20B DW23B

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)												
	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.4	3.6	4.0
10+	4605	5145	5665	6180	6650	7105	7540	8295	8950	9565	9860	10160	10710
10	4085	4620	5105	5560	5980	6380	6725	7370	7960	8505			
30	3240	3660	4045	4405	4740	5060	5330	5840	6310	6745			
40	3025	3420	3780	4115	4430	4725	4985	5460	5895	6300			
50	3025	3420	3780	4115	4430	4725	4985	5460	5895	6300			

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.

Maximum Speed	% change in loads from 40 km/h load	Changes in Infl. Pressure
10	+ 70%	+0.4 bar