

MAXI TRACTION



- Stworzone do ciągników o dużej mocy, kombajnów i żniwiarek
- Podwyższone indeksy nośności i prędkości
- Doskonała trakcja, samooczyszczanie się i komfort prowadzenia
- Długa żywotność opony i równomierne zużywanie się bieżnika

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
650/75R38 169D 166E Maxi Traction	678	1953	883	5885	DW21B	DW20B, DW23B

Tabela Obciążenia i Ciśnięć

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)												
	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0
10+	3755	4565	5310	6010	6675	7310	7710	8285	8630	8960	9270	9575	9860
10	3755	4565	5310	6010	6675	7310	7690	8045	8385	8700			
30	2880	3500	4075	4610	5120	5605	5895	6170	6425	6670			
40	2740	3330	3875	4390	4875	5335	5615	5875	6120	6355			
50	2630	3195	3720	4210	4675	5115	5385	5630	5870	6090			
65		3045	3540	4010	4450	4875	5125	5365	5590	5800			
70		2780	3235	3665	4070	4455	4685	4900	5105	5300			

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.