

MAXI TRACTION



- Stworzone do ciągników o dużej mocy, kombajnów i żniwiarek
- Podwyższone indeksy nośności i prędkości
- Doskonała trakcja, samooczyszczanie się i komfort prowadzenia
- Długa żywotność opony i równomierne zużywanie się bieżnika

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
650/85R38 173D 170E Maxi Traction	712	2067	935	6218	DW23B	DW20B - DW21B

Tabela Obciążenia i Ciśnienia

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)												
	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0
10+	4085	5160	5960	6690	7385	8045	8675	9285	9670	10040	10390	10725	11050
10	4085	4910	5660	6360	7020	7645	8045	8415	8770	9100			
30	3355	4030	4650	5225	5765	6280	6605	6915	7200	7475			
40	3195	3840	4425	4975	5490	5980	6290	6585	6860	7120			
50	3060	3680	4245	4770	5265	5735	6035	6310	6575	6825			
65		3505	4045	4545	5015	5460	5745	6010	6265	6500			
70		3235	3730	4195	4630	5040	5305	5550	5780	6000			

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.