

MAXI TRACTION



- Stworzone do ciągników o dużej mocy, kombajnów i żniwiarek
- Podwyższone indeksy nośności i prędkości
- Doskonała trakcja, samooczyszczanie się i komfort prowadzenia
- Długa żywotność opony i równomierne zużywanie się bieżnika

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
710/70R38 171D 168E Maxi Traction	724	1950	879	5872	DW23B	DW25B

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)												
	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0
10+	4340	5015	5820	6575	7290	7975	8420	9040	9350	9645	9930	10200	10455
10	4340	5015	5820	6575	7290	7975	8320	8640	8945	9225			
30	3330	3845	4465	5045	5590	6115	6380	6625	6855	7075			
40	3170	3660	4250	4800	5325	5820	6075	6310	6530	6735			
50	3040	3510	4075	4605	5105	5585	5825	6050	6260	6460			
65		3340	3880	4385	4860	5315	5545	5760	5960	6150			
70		3045	3535	3995	4425	4840	5050	5245	5430	5600			

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.