

# MAXI TRACTION



- Stworzone do ciągników o dużej mocy, kombajnów i żniwiarek
- Podwyższone indeksy nośności i prędkości
- Doskonała trakcja, samooczyszczanie się i komfort prowadzenia
- Długa żywotność opony i równomierne zużywanie się bieżnika

## Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
710/70R42 173D 170E Maxi Traction	730	2075	938	6217	DW23B	DW25B

## Tabela Obciążenia i Ciśnienia

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)												
	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0
10+	4565	5275	6080	6835	7625	8425	8825	9555	9885	10200	10495	10780	11050
10	4565	5275	6080	6835	7625	8425	8790	9130	9450	9750			
30	3500	4040	4660	5240	5845	6460	6740	7000	7245	7475			
40	3335	3850	4440	4990	5565	6155	6420	6665	6900	7120			
50	3200	3690	4260	4785	5340	5900	6155	6395	6615	6825			
65		3515	4055	4560	5085	5620	5865	6090	6300	6500			
70		3245	3745	4205	4695	5185	5410	5620	5815	6000			

(\*): Cyclic Application (see note)

Note:

- \* Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- \* Vehicles must be unloaded before transport outside the field.
- \* Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- \* Maximum load per tyre includes all possible field and vehicle/usage variations.
- \* For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- \* Basic inflation pressure must be increased as per tables.