



**GALAXY
 AGRICULTURE**

TRA: **R-1**
 Speed Rating: **A8**



Optimised 45 degree lug angle ensures good roadability while on the road and superior self cleaning in the field. Tire life is enhanced by compound designed for low wear, additional rubber at lug centre, stabilised lugs at centre by evenly distributed tie bar. Specially designed lug angles and radius prevents lug base cracks. Additional rubber layer improves penetration resistance. Tougher sidewall provides deflection stability and protection from external damages.

TRACTOR DIAGONAL - 12.4-24

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Mixed application					
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
12.4-24	W11L	315	1160	543	3565	8PR 121A8	1	2050	1340	1090	950	890	NA
							1.5	2600	1700	1390	1210	1130	NA
							2	3080	2010	1650	1430	1340	NA
							2.3	3340	2180	1780	1550	1450	NA
						12PR 129A8	0.8	1790	1090	940	830	780	700
							1.5	2580	1570	1340	1200	1120	1010
							2	3060	1860	1600	1420	1330	1200
							2.5	3500	2130	1820	1630	1520	1370
							3	3890	2370	2030	1810	1690	1520
							3.5	4260	2780	2280	1980	1850	1670

