



**GALAXY
 AGRICULTURE**

TRA: **R-1**
 Speed Rating: **A8**



Optimised 45 degree lug angle ensures good roadability while on the road and superior self cleaning in the field. Tire life is enhanced by compound designed for low wear, additional rubber at lug centre, stabilised lugs at centre by evenly distributed tie bar. Specially designed lug angles and radius prevents lug base cracks. Additional rubber layer improves penetration resistance. Tougher sidewall provides deflection stability and protection from external damages.

TRACTOR - 12.4-36

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		Speed												
		Tractor Applications												
		SW mm	OD mm					Static kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph
12.4-36	W11X36 DW11X36, W10X36	315	1464	681	4408	8 126A8	0.8	2047	1335	1193	1095	988	952	890
							1.2	2599	1695	1514	1390	1254	1209	1130
							1.6	3082	2010	1796	1648	1487	1434	1340
							2	3519	2295	2050	1882	1698	1637	1530
							2.4	3910	2550	2278	2091	1887	1819	1700

