



**GALAXY
 AGRICULTURE**

TRA: **R-1**
 Speed Rating: **A8**



Optimised 45 degree lug angle ensures good roadability while on the road and superior self cleaning in the field. Tire life is enhanced by compound designed for low wear, additional rubber at lug centre, stabilised lugs at centre by evenly distributed tie bar. Specially designed lug angles and radius prevents lug base cracks. Additional rubber layer improves penetration resistance. Tougher sidewall provides deflection stability and protection from external damages.

TRACTOR DIAGONAL - 13.6-24

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
		SW mm	OD mm					Speed				
								Mixed application				
Static kmph	10 kmph	20 kmph	30 kmph	40 kmph								
13.6-24	W12	345	1210	550	3630	8PR	1	2370	1550	1270	1100	1030
						123A8	1.4	2900	1890	1550	1350	1260
						1.8	3360	2190	1800	1560	1460	
						2	3570	2330	1910	1660	1550	

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Mixed Application					
Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph								
13.6-24	W12x24	345	1210	550	3630	8PR	0.8	2090	1270	1090	970	910	820
						123A8	1.2	2650	1610	1380	1230	1150	1040
						1.6	3130	1900	1630	1460	1360	1220	
						2	3570	2330	1910	1660	1550	1400	

