



**GALAXY
 AGRICULTURE**

TRA: **R-1**
 Speed Rating: **A8**



Optimised 45 degree lug angle ensures good roadability while on the road and superior self cleaning in the field. Tire life is enhanced by compound designed for low wear, additional rubber at lug centre, stabilised lugs at centre by evenly distributed tie bar. Specially designed lug angles and radius prevents lug base cracks. Additional rubber layer improves penetration resistance. Tougher sidewall provides deflection stability and protection from external damages.

TRACTOR DIAGONAL - 18.4-30

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Mixed application					
Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph								
18.4-30	W16L	467	1550	696	4545	12 149A8	0.8	3010	1830	1570	1400	1310	1180
							1	3430	2090	1790	1590	1490	1340
							1.2	3820	2320	1990	1780	1660	1490
							2.3	5590	3650	2990	2600	2430	2190

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
		SW mm	OD mm					Speed				
								Mixed Application				
Static kmph	10 kmph	20 kmph	30 kmph	40 kmph								
18.4-30	W16L	465	1550	695	4545	8 139A8	1	4600	3000	2460	2140	2000
							1.4	5590	3650	2990	2600	2430
							1.5	5820	3800	3110	2710	2530
							2	6880	4490	3680	3200	2990

