



**GALAXY
 AGRICULTURE**

TRA: **R-1**
 Speed Rating: **A8**



Optimised 45 degree lug angle ensures good roadability while on the road and superior self cleaning in the field. Tire life is enhanced by compound designed for low wear, additional rubber at lug centre, stabilised lugs at centre by evenly distributed tie bar. Specially designed lug angles and radius prevents lug base cracks. Additional rubber layer improves penetration resistance. Tougher sidewall provides deflection stability and protection from external damages.

TRACTOR DIAGONAL - 18.4-34

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Mixed application					
Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph								
18.4-34	W16L	467	1660	740	4910	8PR	0.8	4390	2870	2350	2040	1910	NA
							1	5010	3270	2680	2330	2180	NA
						142A8	1.2	5570	3630	2980	2590	2420	NA
							1.4	6100	3980	3260	2840	2650	NA
						14PR	0.8	4300	2620	2240	2000	1870	1680
							1.3	5730	3490	2990	2660	2490	2240
						153A8	1.9	7150	4350	3730	3330	3110	2800
							2.5	8400	5480	4490	3910	3650	3290

