


**GALAXY
EARTHMOVER &
MINING**

TRA: **E-4/L-4**
Speed Rating: **B**

ALL
STEEL

SPECIAL
COMPOU
ND


TUBE LESS

HTSR 400 is specially built for dump trucks that face extreme environments while hauling heavy loads. High tread depth ensures consistent traction and greater cut resistance making it the more productive choice. The presence of special compound ensures minimum heat build-up while performing longer runs. Superior cut & chip protection with optimized belt design provides excellent durability resulting in reduced downtime.

Wheel Loader - 29.5R25

| Size | Rim Size inch | TRA Code | Tire Type | TKPH | NSD mm | Unloaded Dimension | | Loaded Static radius mm | Rolling Circumference mm | Load Index PR Symbols | Inflation Pressure bar | Load capacity | | | | | | | | |
|---------|---------------|----------|-----------|------|--------|--------------------|-------|-------------------------|--------------------------|-----------------------|------------------------|---------------|----------|--------|---------|---------|---------|---------|---------|---------|
| | | | | | | SW mm | OD mm | | | | | Speed | | | | | | | | |
| | | | | | | | | | | | | Static kmph | NaN kmph | 5 kmph | 10 kmph | 15 kmph | 20 kmph | 25 kmph | 30 kmph | 40 kmph |
| 29.5R25 | 25.00/3.5 | E-4/L-4 | TL | | 57 | 760 | 1890 | 865 | 5550 | 200B 216A2 | 6.5 | 35840 | 29120 | 25540 | 22400 | 19500 | 18820 | 17920 | 17250 | 15680 |

| Size | Rim Size inch | TRA Code | Tire Type | TKPH | NSD mm | Unloaded Dimension | | Loaded Static radius mm | Rolling Circumference mm | Load Index PR Symbols | Inflation Pressure bar | Load capacity | | | | | | | | |
|---------|---------------|----------|-----------|------|--------|--------------------|-------|-------------------------|--------------------------|-----------------------|------------------------|---|------------|--------|---------|---------|---------|---------|---------|---------|
| | | | | | | SW mm | OD mm | | | | | Speed | | | | | | | | |
| | | | | | | | | | | | | Load capacity for Loader application kg (lbs) | | | | | | | | |
| | | | | | | | | | | | | Static kmph | Creep kmph | 5 kmph | 10 kmph | 15 kmph | 20 kmph | 25 kmph | 30 kmph | 40 kmph |
| 29.5R25 | 25.00/3.5 | E-4/L-4 | TL | | 0 | 765 | 1890 | 852.2 | 5611 | 216A2 | 6.5 | 35500 | 29000 | 25750 | 22400 | 19500 | 18500 | 18000 | 17000 | 16000 |

