



GALAXY **AGRICULTURE**

TRA: **I-3** Speed Rating: **A8**

TL
TUBE LESS

Galaxy FLOT PRO is specially designed for low end applications like balers, wagons and other agricultural implements. It displays excellent flotation and self cleaning characteristics. The tire has moderate traction flotation profile and provides maximum soil protection and low soil compaction.

IMPLEMENTS - 400/60-15.5

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								Drive Wheel				Free Rolling			
		SW mm	OD mm					10 kmph	25 kmph	40 kmph	50 kmph	10 kmph	25 kmph	40 kmph	50 kmph
400/60- 15.5	13.00DC	404	874	377	2510	16PR 148A8	1	1320	1120	940	846	1860	1580	1330	1200
							2	1970	1680	1410	1269	2790	2370	1990	1790
							2.5	2250	1920	1610	1449	3180	2700	2270	2040
							3.5	2740	2330	1960	1764	3860	3280	2760	2480
							4	2970	2520	2120	1908	4170	3550	2980	2680
							4.4	3140	2670	2240	2016	4410	3750	3150	2840

