



**GALAXY  
 AGRICULTURE**

TRA: **R-1W**  
 Speed Rating: **D**



Earth Pro radial 650 is an extra wide tire available in radial for use in agricultural tractors and combine harvesters for farming. It is characterized by increased load capacity for the same inflation pressure. This means that the low inflation pressure combined with large footprint helps reduce soil compaction. Low angled lugs of the tire at the shoulder area improve traction, while higher angles around the tire center line improve ride comfort. This leads to increased tire traction efficiency by an effective traction/slip characteristic. Also the strong radial construction with reinforced beads and sidewalls provide long tire life.

**TRACTOR - 480/65R24**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
		SW mm	OD mm					Speed									
								1)Not high and sustained torque,2)Road Transport									
								Non cyclic operation									
Field kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph	70 kmph								
480/65R24	W15L W14L	479	1240	557	3749	140D 143A8	1.2	1920	2510	2240	2050	1980	1920	1830	1750	1670	1520
							1.6	2270	2960	2640	2420	2330	2270	2160	2070	1970	1790
							2	2590	3380	3020	2770	2670	2590	2460	2360	2250	2050
							2.4	2880	3750	3350	3080	2960	2880	2740	2630	2500	2280

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
		SW mm	OD mm					Speed	
								1)Not high and sustained torque,2)Road Transport	
								Cyclic operation	
10 kmph	15 kmph								
480/65R24	W15L W14L	479	1240	557	3749	140D 143A8	1.5	2840	2590
							2	3350	3050
							2.5	3830	3490
							3	4250	3880

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

