



**GALAXY  
 AGRICULTURE**

TRA: **R-1W**  
 Speed Rating: **D**



Earth Pro radial 650 is an extra wide tire available in radial for use in agricultural tractors and combine harvesters for farming. It is characterized by increased load capacity for the same inflation pressure. This means that the low inflation pressure combined with large footprint helps reduce soil compaction. Low angled lugs of the tire at the shoulder area improve traction, while higher angles around the tire center line improve ride comfort. This leads to increased tire traction efficiency by an effective traction/slip characteristic. Also the strong radial construction with reinforced beads and sidewalls provide long tire life.

**TRACTOR - 540/65R30**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load										
								Speed										
		1)Not high and sustained torque,2)Road Transport																
		Non cyclic operation																
		SW mm	OD mm					Field kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph	70 kmph	
540/65R30	W16L W18L	550	1486	675	4504	150D 153A8		1.2	2560	3350	2990	2740	2640	2560	2440	2340	2230	2030
								1.6	3040	3960	3540	3250	3130	3040	2890	2770	2640	2400
								2	3460	4520	4030	3700	3570	3460	3300	3160	3010	2740
								2.4	3850	5030	4490	4120	3970	3850	3670	3520	3350	2740

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load		
								Speed		
		1)Not high and sustained torque,2)Road Transport								
		Cyclic operation								
		SW mm	OD mm					10 kmph	15 kmph	
540/65R30	W16L W18L	550	1486	675	4504	150D 153A8		1.5	3790	3460
								2	4490	4090
								2.5	5120	4670
								3	5700	5190

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

