



**GALAXY  
 AGRICULTURE**

TRA: **I-3**  
 Speed Rating: **A8**



Galaxy FLOT PRO is specially designed for low end applications like balers,wagons and other agricultural implements.It displays excellent flotation and self cleaning characteristics. The tire has moderate traction flotation profile and provides maximum soil protection and low soil compaction.

**IMPLEMENTS - 550/60-22.5**

| Size        | Rim     | Unloaded Dimension |       | Loaded Static radius mm | Rolling Circumference mm | Load Index PR Symbols | Inflation Pressure bar | Recommended Load |         |         |         |              |         |         |         |  |  |
|-------------|---------|--------------------|-------|-------------------------|--------------------------|-----------------------|------------------------|------------------|---------|---------|---------|--------------|---------|---------|---------|--|--|
|             |         |                    |       |                         |                          |                       |                        | Speed            |         |         |         |              |         |         |         |  |  |
|             |         |                    |       |                         |                          |                       |                        | Drive Wheel      |         |         |         | Free Rolling |         |         |         |  |  |
|             |         | SW mm              | OD mm |                         |                          |                       |                        | 10 kmph          | 25 kmph | 40 kmph | 50 kmph | 10 kmph      | 25 kmph | 40 kmph | 50 kmph |  |  |
| 550/60-22.5 | 16.00DC | 550                | 1238  | 540                     | 3765                     | 16PR                  | 2.4                    | 4610             | 3920    | 3290    | 2960    | 6510         | 5530    | 4650    | 4190    |  |  |
|             |         |                    |       |                         |                          |                       | 2.6                    | 4830             | 4110    | 3450    | 3110    | 6820         | 5800    | 4870    | 4380    |  |  |
|             |         |                    |       |                         |                          | 166A8                 | 3                      | 5250             | 4460    | 3750    | 3380    | 7420         | 6310    | 5300    | 4770    |  |  |
|             |         |                    |       |                         |                          |                       | 4.1                    | 7510             | 6380    | 5360    | 4830    | 8900         | 7570    | 6360    | 5720    |  |  |

