




GALAXY
MATERIAL HANDLING

TRA: **SOLID**
 Speed Rating: **SOLID**



Lifttop SDS is the latest addition to the Galaxy's extensive range of forklift tires. This non-marking tire is specially designed for forklifts performing severe duty applications in warehouses. The robust 3-stage construction ensures manifold advantages like superior riding comfort, minimum heat build up, enhanced shock absorption and excellent durability. Special tread design with optimum tread depth ensures grip and stability.

INDUSTRIAL FORKLIFT TIRES - 6.50-10

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
								Speed	
		SW mm	OD mm					Load Wheel	Steer Wheel
								25 kmph	25 kmph
6.50-10	5.50F-10	160	566				0	2340	1800

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
								Speed	
		SW mm	OD mm					Load Wheel	Steer Wheel
								25 kmph	25 kmph
6.50-10	5.00F-10	160	566				0	2340	1800

All sizes are available in standard heel and quick heel.

