



10-16.5

IT323 • 135A2 • SS



TECHNICAL DATA

Design	IT323	Static Loaded Radius mm	346*
Industry Classification	SS	Rolling Circ mm	2304*
Tyre Size	10-16.5	SRI	n/a
LI/SS	135A2	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	520
PR	10	Max Load kg	2180
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	264*	Recom'd Rim	8.25
Overall Diameter mm	773*	Other approved rims	n/a

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	140kpa	170kpa	240kpa	280kpa	310kpa	340kpa	380kpa	410kpa	450kpa	520kpa	550kpa
10	815	940	1125	1220	1325	1400	1475	1565	1605	1750†	n/a
5	945	1090	1305	1415	1535	1625	1710	1815	1865	2030	n/a
20	710	820	980	1065	1155	1220	1285	1365	1400	1525	n/a
25	690	795	955	1035	1125	1185	1250	1325	1360	1485	n/a
30	675	780	935	1015	1100	1165	1225	1300	1335	1455	n/a
40	650	750	900	975	1060	1120	1180	1250	1285	1400	n/a
10cycl	975	1125	1350	1465	1590	1680	1770	1875	1930	2100	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor