



# 11.2-28

Sure Grip All Service • 108A8 • R-1



## TECHNICAL DATA

|                         |                       |                                |       |
|-------------------------|-----------------------|--------------------------------|-------|
| Design                  | Sure Grip All Service | Static Loaded Radius mm        | 541   |
| Industry Classification | R-1                   | Rolling Circ mm                | 3607  |
| Tyre Size               | 11.2-28               | SRI                            | 575   |
| LI/SS                   | 108A8                 | Weight kg                      | 39.38 |
| FR/DW                   | n/a                   | Nominal Inflation Pressure kPa | 180   |
| PR                      | 6                     | Max Load kg                    | 1000  |
| TL/TT                   | TT                    | Tread Depth mm                 | n/a   |
| Section Width mm        | 305                   | Recom'd Rim                    | W10   |
| Overall Diameter mm     | 1206                  | Other approved rims            | W9    |

## LOAD DATA

| Max Speed (km/h) | Tyre load (kg) at various inflation pressures (kPa) |        |        |        |        |        |        |        |        |        |        |
|------------------|---|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
|                  | 80kpa   | 100kpa | 140kpa | 150kpa | 170kpa | 180kpa | 190kpa | 210kpa | 220kpa | 250kpa | 280kpa |
| 40               | 630   | 690    | 875    | 900    | 950    | 1000†  | n/a    | n/a    | n/a    | n/a    | n/a    |
| 25               | 700   | 765    | 970    | 1000   | 1055   | 1120   | n/a    | n/a    | n/a    | n/a    | n/a    |

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor