



12-16.5

IT323 • 145A2 • SS



TECHNICAL DATA

Design	IT323	Static Loaded Radius mm	369*
Industry Classification	SS	Rolling Circ mm	2458*
Tyre Size	12-16.5	SRI	n/a
LI/SS	145A2	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	550
PR	12	Max Load kg	2900
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	307*	Recom'd Rim	9.75
Overall Diameter mm	831*	Other approved rims	n/a

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	140kpa	170kpa	240kpa	280kpa	310kpa	340kpa	380kpa	410kpa	450kpa	520kpa	550kpa
10	1065	1190	1475	1565	1700	1815	1875	2000	2125	2250	2375†
5	875	980	1215	1290	1400	1495	1545	1650	1750	1855	1955
20	925	1035	1285	1365	1480	1580	1635	1745	1855	1960	2070
25	900	1005	1250	1325	1440	1535	1590	1695	1800	1910	2015
30	885	990	1225	1300	1415	1510	1560	1665	1770	1870	1975
40	850	950	1180	1250	1360	1450	1500	1600	1700	1800	1900
10cycl	1275	1425	1770	1875	2040	2175	2250	2400	2550	2700	2850

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor