



# 12.4-28

Sure Grip All Service • 118A8 • R-1



## TECHNICAL DATA

Design	Sure Grip All Service	Static Loaded Radius mm	566
Industry Classification	R-1	Rolling Circ mm	3770
Tyre Size	12.4-28	SRI	600
LI/SS	118A8	Weight kg	44.97
FR/DW	n/a	Nominal Inflation Pressure kPa	165
PR	6	Max Load kg	1320
TL/TT	TT	Tread Depth mm	n/a
Section Width mm	313	Recom'd Rim	W11
Overall Diameter mm	1255	Other approved rims	W12

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	80kpa	100kpa	140kpa	150kpa	170kpa	180kpa	190kpa	210kpa	220kpa	250kpa	280kpa
40	775	850	1030	1090	1150†	n/a	n/a	n/a	n/a	n/a	n/a
25	860	945	1145	1210	1285	n/a	n/a	n/a	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor