



16.9-28

Sure Grip Industrial Tractor • 152A8 • R-4



TECHNICAL DATA

Design	Sure Grip Industrial Tractor	Static Loaded Radius mm	628*
Industry Classification	R-4	Rolling Circ mm	4189*
Tyre Size	16.9-28	SRI	n/a
LI/SS	152A8	Weight kg	103.87*
FR/DW	n/a	Nominal Inflation Pressure kPa	260
PR	12	Max Load kg	3550
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	437*	Recom'd Rim	W15L
Overall Diameter mm	1420*	Other approved rims	W14L

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	120kpa	140kpa	150kpa	170kpa	180kpa	190kpa	210kpa	220kpa	230kpa	250kpa	260kpa
50	1875	2040	2150	2345	2480	2550	2730	2800	2960	3050	3140
40	2060	2240	2360	2575	2725	2800	3000	3075	3250	3350	3450†
30	2140	2330	2455	2680	2835	2910	3120	3200	3380	3485	3590
20	2245	2440	2570	2805	2970	3050	3270	3350	3545	3650	3760
10	2575	2800	2950	3220	3405	3500	3750	3845	4065	4190	4315
5	2985	3250	3420	3735	3950	4060	4350	4460	4715	4860	5005
10cycl	3090	3360	3540	3865	4090	4200	4500	4615	4875	5025	5175
5cycl	3440	3740	3940	4300	4550	4675	5010	5135	5430	5595	5760

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor