



320/85R24

Optitrac • 122D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	518
Industry Classification	R-1W	Rolling Circ mm	3454
Tyre Size	320/85R24	SRI	550
LI/SS	122D	Weight kg	60.85
FR/DW	n/a	Nominal Inflation Pressure kPa	160
PR	n/a	Max Load kg	1500
TL/TT	TL	Tread Depth mm	41.27
Section Width mm	318	Recom'd Rim	W10
Overall Diameter mm	1151	Other approved rims	W9, W11

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	220kpa	240kpa	260kpa
70	n/a	n/a	990	1105	1240	1365	n/a	n/a	n/a	n/a	n/a
65	n/a	n/a	1090	1215	1360	1500	n/a	n/a	n/a	n/a	n/a
50	825	n/a	1145	1275	1430	1575	n/a	n/a	n/a	n/a	n/a
40	n/a	1040	1195	1330	1490	1645	n/a	n/a	n/a	n/a	n/a
30	950	1095	1255	1395	1565	1725	n/a	n/a	n/a	n/a	n/a
10	1200	1515	1645	1780	1910	2040	2470	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	1835	1980	2120	2265	2480	2550	n/a	n/a	n/a

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor