



340/85R24

Optitrac • 130D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	549
Industry Classification	R-1W	Rolling Circ mm	3606
Tyre Size	340/85R24	SRI	575
LI/SS	130D	Weight kg	66
FR/DW	n/a	Nominal Inflation Pressure kPa	240
PR	n/a	Max Load kg	1900
TL/TT	TL	Tread Depth mm	39
Section Width mm	349	Recom'd Rim	W12
Overall Diameter mm	1181	Other approved rims	W11

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	220kpa	240kpa	260kpa
70	n/a	n/a	1075	1240	1365	1500	1545	1640	1685	1730	n/a
65	n/a	1030	1180	1360	1500	1650	1700	1800	1850	1900†	n/a
50	n/a	1080	1240	1430	1575	1735	1785	1890	1945	1995	n/a
40	n/a	1130	1290	1490	1645	1805	1860	1970	2025	2080	n/a
30	1020	1185	1355	1565	1725	1895	1955	2070	2130	2185	n/a
10	1330	1545	1770	2040	2250	2475	2550	2700	2775	2850	n/a
10cycl	n/a	n/a	1750	2085	2295	2440	2595	2805	2840	2940	3035

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor