



340/85R28

Optitrac • 127D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	579
Industry Classification	R-1W	Rolling Circ mm	3858
Tyre Size	340/85R28	SRI	625
LI/SS	127D	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	160
PR	n/a	Max Load kg	1750
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	341	Recom'd Rim	W12
Overall Diameter mm	1294	Other approved rims	W11

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	220kpa	240kpa	260kpa
70	n/a	1025	1285	1450	1600	1595	n/a	n/a	n/a	n/a	n/a
65	n/a	1120	1285	1450	1600	1750†	n/a	n/a	n/a	n/a	n/a
50	n/a	1175	1350	1525	1680	1840	n/a	n/a	n/a	n/a	n/a
40	n/a	1225	1405	1590	1750	1915	n/a	n/a	n/a	n/a	n/a
30	1095	1290	1480	1665	1840	2010	n/a	n/a	n/a	n/a	n/a
10	1425	1680	1930	2175	2400	2625	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	1905	2330	2490	2650	2815	2975	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor