



# 440/65R28

Optitrac • 131D • R-1W



## TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	588
Industry Classification	R-1W	Rolling Circ mm	3890
Tyre Size	440/65R28	SRI	625
LI/SS	131D	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	160
PR	n/a	Max Load kg	1950
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	422	Recom'd Rim	W14L
Overall Diameter mm	1280	Other approved rims	W13, W14L, W15L

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	260kpa	280kpa
70	n/a	1170	1320	1500	1640	1775	n/a	n/a	n/a	n/a	n/a
65	n/a	1285	1450	1650	1800	1950†	n/a	n/a	n/a	n/a	n/a
50	n/a	1350	1525	1735	1890	2050	n/a	n/a	n/a	n/a	n/a
40	n/a	1405	1590	1805	1970	2135	n/a	n/a	n/a	n/a	n/a
30	1255	1480	1665	1895	2070	2245	n/a	n/a	n/a	n/a	n/a
10	1635	1930	2175	2475	2700	2925	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	2185	2595	2775	2955	3135	3315	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor