



# 460/70R24

IT520 • 159A8/B • R-4



## TECHNICAL DATA

Design	IT520	Static Loaded Radius mm	n/a
Industry Classification	R-4	Rolling Circ mm	n/a
Tyre Size	460/70R24	SRI	600
LI/SS	159A8/B	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	400
PR	n/a	Max Load kg	4375
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	469	Recom'd Rim	DW15L
Overall Diameter mm	1255	Other approved rims	W15L, W16L

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	140kpa	180kpa	200kpa	220kpa	240kpa	260kpa	280kpa	300kpa	320kpa	360kpa	400kpa
50	1900	2240	2430	2650	2800	3000	3250	3450	3550	4000	4375†
40	1620	1970	2190	2450	2670	2800	2930	3195	3455	3895	4375
30	1685	2050	2280	2550	2775	2910	3045	3325	3595	4050	4550
15cycl	2170	2640	2935	3285	3580	3750	3925	4280	4630	5220	5865
10cycl	2430	2955	3285	3675	4005	4200	4395	4795	5185	5845	6565

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor