



480/65R28

Optitrac • 136D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	614
Industry Classification	R-1W	Rolling Circ mm	4061
Tyre Size	480/65R28	SRI	650
LI/SS	136D	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	160
PR	n/a	Max Load kg	2240
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	476	Recom'd Rim	W15L
Overall Diameter mm	1336	Other approved rims	W14L, W15L

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	260kpa	280kpa
70	n/a	1320	1500	1730	1875	2040	n/a	n/a	n/a	n/a	n/a
65	n/a	1450	1650	1900	2060	2240†	n/a	n/a	n/a	n/a	n/a
50	n/a	1525	1735	1995	2165	2350	n/a	n/a	n/a	n/a	n/a
40	n/a	1590	1805	2080	2255	2455	n/a	n/a	n/a	n/a	n/a
30	1440	1665	1895	2185	2370	2575	n/a	n/a	n/a	n/a	n/a
10	1875	2175	2475	2850	3090	3360	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	2465	2985	3190	3395	3605	3810	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor