



# 540/65R24

Optitrac • 146A8/B • R-1W



## TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	631
Industry Classification	R-1W	Rolling Circ mm	3995
Tyre Size	540/65R24	SRI	625
LI/SS	146A8/B	Weight kg	124
FR/DW	n/a	Nominal Inflation Pressure kPa	240
PR	n/a	Max Load kg	3000
TL/TT	TL	Tread Depth mm	50
Section Width mm	543	Recom'd Rim	W16L
Overall Diameter mm	1330	Other approved rims	W18L

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	260kpa	280kpa
50	n/a	1650	1850	2120	2300	2500	2650	2800	3000	n/a	n/a
40	1400	1650	1850	2120	2300	2500	2650	2800	3000†	n/a	n/a
30	1400	1765	1980	2270	2460	2675	2835	2995	3210	n/a	n/a
10	2100	2475	2775	3180	3450	3750	3975	4200	4500	n/a	n/a
10cycl	n/a	n/a	2805	3305	3635	3870	4100	4250	4640	4795	4945

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor