



# 580/70R38

Optitrac • 155D • R-1W



## TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	821*
Industry Classification	R-1W	Rolling Circ mm	5476*
Tyre Size	580/70R38	SRI	875*
LI/SS	155D	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	160*
PR	n/a	Max Load kg	3875*
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	606*	Recom'd Rim	W18L
Overall Diameter mm	1827*	Other approved rims	n/a

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	120kpa	140kpa	160kpa	200kpa	220kpa	240kpa	280kpa	300kpa	320kpa
70	n/a	2275	2865	3230	3525	n/a	n/a	n/a	n/a	n/a	n/a
65	n/a	2500	3150	3550	3875†	n/a	n/a	n/a	n/a	n/a	n/a
50	n/a	2625	3310	3730	4070	n/a	n/a	n/a	n/a	n/a	n/a
40	n/a	2740	3450	3885	4245	n/a	n/a	n/a	n/a	n/a	n/a
30	2440	2875	3620	4080	4455	n/a	n/a	n/a	n/a	n/a	n/a
10	3180	3750	4725	5325	5815	n/a	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	5160	5515	5870	6590	n/a	n/a	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor