



600/65R28

Optitrac • 154D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	685
Industry Classification	R-1W	Rolling Circ mm	4556
Tyre Size	600/65R28	SRI	700
LI/SS	154D	Weight kg	169
FR/DW	n/a	Nominal Inflation Pressure kPa	240
PR	n/a	Max Load kg	3750
TL/TT	TL	Tread Depth mm	51
Section Width mm	587	Recom'd Rim	W18L
Overall Diameter mm	1504	Other approved rims	DW20B

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	280kpa	320kpa
70	n/a	n/a	2150	2410	2640	2800	3050	3230	3415	n/a	n/a
65	n/a	2060	2360	2650	2900	3075	3350	3550	3750†	n/a	n/a
50	n/a	2165	2480	2785	3045	3230	3520	3730	3940	n/a	n/a
40	n/a	2255	2585	2900	3175	3365	3670	3885	4105	n/a	n/a
30	2015	2370	2715	3045	3335	3535	3850	4080	4315	n/a	n/a
10	2625	3090	3540	3975	4350	4615	5025	5325	5625	n/a	n/a
10cycl	n/a	n/a	3500	4130	4545	4840	5125	5230	5800	6185	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor