



# 600/65R38

Optitrac • 153D • R-1W



## TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	806
Industry Classification	R-1W	Rolling Circ mm	5321
Tyre Size	600/65R38	SRI	825
LI/SS	153D	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	160
PR	n/a	Max Load kg	3650
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	573	Recom'd Rim	W18L
Overall Diameter mm	1748	Other approved rims	DW20B

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	260kpa	280kpa
70	n/a	2150	2480	2800	3050	3320	n/a	n/a	n/a	n/a	n/a
65	2060	2360	2725	3075	3350	3650†	n/a	n/a	n/a	n/a	n/a
50	n/a	2480	2860	3230	3520	3835	n/a	n/a	n/a	n/a	n/a
40	n/a	2585	2985	3365	3670	3995	n/a	n/a	n/a	n/a	n/a
30	2370	2715	3135	3535	3850	4200	n/a	n/a	n/a	n/a	n/a
10	3090	3540	4090	4615	5025	5475	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	4010	4860	5195	5530	5870	6205	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor