



600/70R30

Optitrac • 158D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	732
Industry Classification	R-1W	Rolling Circ mm	4909
Tyre Size	600/70R30	SRI	750
LI/SS	158D	Weight kg	205
FR/DW	n/a	Nominal Inflation Pressure kPa	240
PR	n/a	Max Load kg	4250
TL/TT	TL	Tread Depth mm	52
Section Width mm	608	Recom'd Rim	DW20B
Overall Diameter mm	1629	Other approved rims	DW18L

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	280kpa	320kpa
70	n/a	n/a	2410	2730	3050	3230	3525	3640	3870	n/a	n/a
65	n/a	2360	2650	3000	3350	3550	3875	4000	4250†	n/a	n/a
50	n/a	2480	2785	3150	3520	3730	4070	4200	4465	n/a	n/a
40	n/a	2585	2900	3285	3670	3885	4245	4380	4655	n/a	n/a
30	2285	2715	3045	3450	3850	4080	4455	4600	4890	n/a	n/a
10	2975	3540	3975	4500	5025	5325	5815	6000	6375	n/a	n/a
10cycl	n/a	n/a	4010	4685	5150	5485	5810	6035	6575	7010	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor