



620/75R26

Optitrac • 166B • R1-W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	700
Industry Classification	R1-W	Rolling Circ mm	4726
Tyre Size	620/75R26	SRI	750
LI/SS	166B	Weight kg	215
FR/DW	n/a	Nominal Inflation Pressure kPa	320
PR	n/a	Max Load kg	5300
TL/TT	TL	Tread Depth mm	57
Section Width mm	624	Recom'd Rim	DW20B
Overall Diameter mm	1574	Other approved rims	n/a

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	280kpa	320kpa
50	n/a	2500	2800	3150	3550	3650	4125	4250	4500	5000	5300
40	n/a	2500	2800	3150	3550	3650	4125	4250	4500	5000	5300†
30	2270	2675	2995	3370	3800	3905	4415	4550	4815	5350	5670
10	3180	3750	4200	4725	5325	5475	6190	6375	6750	7500	7950
10cycl	n/a	n/a	4250	4955	5455	5805	6150	6205	6960	7420	7920

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor