



**620/75R30**

Optitrac • 163B • R1-W



## TECHNICAL DATA

Design	<b>Optitrac</b>	Static Loaded Radius mm	<b>757</b>
Industry Classification	<b>R1-W</b>	Rolling Circ mm	<b>5034</b>
Tyre Size	<b>620/75R30</b>	SRI	<b>800</b>
LI/SS	<b>163B</b>	Weight kg	<b>269</b>
FR/DW	<b>n/a</b>	Nominal Inflation Pressure kPa	<b>240</b>
PR	<b>n/a</b>	Max Load kg	<b>4875</b>
TL/TT	<b>TL</b>	Tread Depth mm	<b>59</b>
Section Width mm	<b>636</b>	Recom'd Rim	<b>DW20B</b>
Overall Diameter mm	<b>1661</b>	Other approved rims	<b>n/a</b>

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	280kpa	320kpa
50	n/a	2650	3000	3350	3750	3875	4375	4500	4875	n/a	n/a
40	n/a	2650	3000	3350	3750	3875	4375	4500	4875†	n/a	n/a
30	2395	2835	3210	3585	4015	4145	4680	4815	5215	n/a	n/a
10	3360	3975	4500	5025	5625	5815	6565	6750	7315	n/a	n/a
10cycl	n/a	n/a	4505	5370	5910	6290	6665	6590	7545	8040	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor