



800/65R32

Optitrac • 172A8 • R1-W



TECHNICAL DATA

| | | | |
|-------------------------|------------------|--------------------------------|--------------|
| Design | Optitrac | Static Loaded Radius mm | 805 |
| Industry Classification | R1-W | Rolling Circ mm | 5420 |
| Tyre Size | 800/65R32 | SRI | 875 |
| LI/SS | 172A8 | Weight kg | 322 |
| FR/DW | n/a | Nominal Inflation Pressure kPa | 240 |
| PR | n/a | Max Load kg | 6300 |
| TL/TT | TL | Tread Depth mm | 60.5 |
| Section Width mm | 769 | Recom'd Rim | DW27B |
| Overall Diameter mm | 1823 | Other approved rims | DH27B |

LOAD DATA

| Max Speed (km/h) | Tyre load (kg) at various inflation pressures (kPa) | | | | | | | | | | |
|------------------|---|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| | 60kpa | 80kpa | 100kpa | 120kpa | 140kpa | 160kpa | 180kpa | 200kpa | 240kpa | 280kpa | 320kpa |
| 50 | n/a | 3450 | 4000 | 4375 | 4875 | 5450 | 5600 | 5800 | 6300 | n/a | n/a |
| 40 | 3000 | 3450 | 4000 | 4375 | 4875 | 5450 | 5600 | 5800 | 6300† | n/a | n/a |
| 30 | 3210 | 3690 | 4280 | 4680 | 5215 | 5830 | 5990 | 6205 | 6740 | n/a | n/a |
| 10 | 4500 | 5175 | 6000 | 6565 | 7315 | 8175 | 8400 | 8700 | 9450 | n/a | n/a |
| 10cycl | n/a | n/a | 5865 | 6940 | 7635 | 8130 | 8610 | 9265 | 9745 | 10390 | n/a |

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor