

SPECIFICATIONS

# AGRIXTRA

## 65 SERIES

### FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions mean stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
440/65R28	131D / 134A8	TL	W14L	W13	42

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rolling Circumference Index	75% of Internal volume (l)
442	1283	579	3836	625	39	179

Max load per tyre (kg) / Inflation pressure (bar)									
	(km/h)	0.6	0.8	1	1.2	1.4	1.6	1.8	1.9
Service Speed (km/h)	<b>10 LT</b>	1575	1785	1995	2205	2415	2625		2925
	<b>30 LT / 10 HT</b>	1345	1525	1705	1885	2065	2245		
	<b>40</b>		1450	1625	1795	1965	2120		
	<b>50</b>		1390	1555	1720	1885	2050		
	<b>65</b>			1480	1640	1795	1950		