

SPECIFICATIONS

AGRIXTRA 65 SERIES

FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions mean stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
600/65R38	153D / 156A8	TL	DW20B	W18L	51

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rolling Circumference Index	75% of Internal volume (l)
611	1745	787	5218	825	45	490

Max load per tyre (kg) / Inflation pressure (bar)									
	(km/h)	0.6	0.8	1	1.2	1.4	1.6	1.8	1.9
Service Speed (km/h)	10 LT	2945	3340	3730	4125	4515	4910		5475
	30 LT / 10 HT	2520	2855	3190	3525	3860	4200		
	40		2720	3040	3355	3675	4000		
	50		2605	2915	3220	3525	3835		
	65			2775	3065	3360	3650		