

SPECIFICATIONS

AGRIXTRA

65 SERIES

FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions mean stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
650/65R38	157D / 160A8	TL	DW20B	DW20A	56

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rolling Circumference Index	75% of Internal volume (l)
645	1810	812	5412	875	46	573

Max load per tyre (kg) / Inflation pressure (bar)									
	(km/h)	0.6	0.8	1	1.2	1.4	1.6	1.8	1.9
Service Speed (km/h)	10 LT	3330	3775	4215	4660	5105	5550		6190
	30 LT / 10 HT	2845	3225	3605	3985	4365	4745		
	40		3070	3435	3795	4155	4500		
	50		2945	3290	3640	3985	4330		
	65			3135	3465	3795	4125		